

IKOS900

Wall-mounted hood box made of stainless steel or steel
900 mm



Stainless steel (900 mm)



EVO ENGINE

Alternative Current motor with reduced noise level at the lowest speeds



BOOSTER FUNCTION

Superior and timed hood performance over a maximum period of 6 minutes



HIGH PERFORMANCE FILTER (option)

Efficient and economical solution, the high-performance filters are dishwasher-safe and self-regenerating. They have a lifespan of approximately 3 years

CONTROLS

Control type	Electronic
Number of speeds	3 + boost

FILTRATION

Grease filter	Aluminium
Number of grease filters	1
Charcoal filter	Optional (x1)

ENERGY EFFICIENCY

Energy Efficiency Class	A
Lighting Efficiency (LE) Lux/Watt	58
Lighting Efficiency Class	A

PERFORMANCES

	Min	Mid	Max	boost
Capacity point suction IEC (m3/h)	303	436	602	741
Power (Watts)	173	215	258	270
Pressure (BP)	428	487	521	533
Noise level dB (A)	49	58	65	70
Noise pressure (dB(A))	43	52	59	64

LIGHT

Light	Spot LED
Number of lamps and power + Kelvin	2 x 1 W (4000K)
Dimmer	No

IKOS

TECHNICAL DATA

Frequency (Hz)	50 - 60
Fuse (A)	10
Voltage (V)	220 - 240
Electrical wire	Included

INSTALLATION

Mode	Ducting or recycling
Installation without chimney	N/A
Installation height (min, mm)	650 mini
Outlet diameter (mm)	Ø150

DIMENSIONS & WEIGHTS

Dimensions of the product without chimney (W x H x D - mm)	898x294x490 (900mm)
Carton dimension (W x H x D - mm)	1010x600x700 mm
Chimney height min-max (mm)	625-985
Gross weight (kg)	25(900mm)
Net weight (kg)	18(900mm)
Band height (mm)	40

