



VCert. 6010761





EAN Code: 3543290003599

CONFIGURATION	Storage shelves	Sliding shelves	Capacity**
Maximum Configuration (100% sliding)	-	13	170
Mixed Configuration	2	4	206
Minimum Configuration (100% storage)	4	0	230
Standard Configuration	4	0	230

## **UNIVERSAL SHELF**

Universal shelf: AOHUI

Weight: 2.6 kg

Type of structure: slats

Number of bottles per level: 12

**Material**: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in





Standard configuration
Traditional Bordeaux bottles



« Sliding»
12 Bottles



« Presentation »

Artevino AOHUI shelf has a label holder:



Description	Reference	EAN Code
Single Solid beechwood universal shelf	AOHUI	3543290002783

Range : OXYGEN

Model : OXGIT230NPD

Fonction: Ageing

Capacity\*: 230 Bottles\*\*

A constant temperature due to the dual Heating/Cooling controls.

Optimised humidity due to the circulation of humid air.



Air circulation ensured by the principle of thermodynamic pump.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a solid door with highly effective LIV filter



## GENERAL FEATURES

Gross weight, packaged(kg)\* : 98,4Net weight (kg)\* : 82,4

Dimensions in packaging H x W x D (mm) :  $1950 \times 720 \times 760$ Dimensions H x W x D(mm) :  $1825 \times 680 \times 700$ 

Color scheme : Black

Energy efficiency rating : A+

Acoustic emissions (dB(A))\*\*\*\*\* : 37

Electrical power (W)\*\*\* : 70

Electrical intensity (A)\*\*\* : 0.33

Consumption per 24h (KWh) \*\*\*\* : 0.35

Annual energy consumption AEc\* (kWh/year) \*\*\*\* : 128

Ambient temperature operating limit : 0 - 35°C

- √ Digital electronic controls
- √ Temperature display on indoor sidewall
- ✓ Double Hot/ Cold circuit > Automatic « Winter function »
- ✓ Temperature fault alarm icon
- √ Interior lining of dimpled aluminium
- ✓ Solid door
- √ Hygrometry ensured by the principle of thermodynamic pump
- ✓ 2 adjustable feet
- ✓ Lock
- √ Storage grid in the low part
- ✓ Inox Handle

Calculated with an ambient temperature of 25°C
 Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration
 R600a gas. With a R134a gas (for US, CA, Korea, Taïwan): 38 db(A)